

Electronic Urinal Flusher



UF502AC

UF502 DC

UF502

Wall Mounted Urinal Flusher



UF508AC

UF508 DC

UF508

Wall Mounted Urinal Flusher

	UF502	UF508
Material	ABS Plastic	ABS Plastic
Dimensions (W x H x D)	165mm x 120mm x 100mm	110mm x 250mm x 120mm
Package	8 sets/ carton	10 sets/ carton
Shipping Weight/Carton	11.0kgs (24.2lbs)	14.7kgs (32.4lbs)
Measurement	1.72 cuft.	2.6 cuft.
Installation Type	Wall Mounted	Wall Mounted
Power Source	AA type x 4 or AC type	AA type x 4 or AC type
Battery Life	3 years (3,000 cycles per month)	3 years (3,000 cycles per month)
Sensing Range	30-70cm (adjustable)	30-70cm (adjustable)
Operating Water Pressure	10 to 100 PSI	10 to 100 PSI
Operating Voltage	110V-220Vac, 50/60 Hz, 6W	110V-220Vac, 50/60 Hz, 6W
Standby Power	0.3W	0.3W
Pre Flush Time	1 Second	1 Second
Main Flush Time	2-16 Sec (adjustable)	2-16 Sec (adjustable)

